
## PRODUCT OVERVIEW - INSTRUMENT ENCLOUSURES CPS-100

PRODUCT DESCRIPTION

## INSTRUMENT ENCLOUSURES BOX CPS-100 - DIMENSION 328 mm (W) x 457 mm (H) x 400 mm (D)

## **CPS-100**



INSTRUMENT PROTECTION BOXES TYPE CPS-100

Are designed to for n.1 instrument with manifold and our full range of optional accessories.

The boxes are made in polyester reinforced fiber glass, 5 mm thickness, colour grey RAL 7035.

Are made with the junction of a lower fixed half shell with an upper mobile half shell.

The protection boxes are provided with a steel arm that ensures secure opening of the top shell

The neoprene gasket assembled on the lower part guarantees the seal and a perfect impermeability to liquids and dust.

The closing of the box is ensured by stainless steel fasteners on the sides.



The material has the following characteristics

- Weather Protection IP-65
- Impact resistance
- Austenic stainless steel fitting and fixings
- Non-absorption of hydrocarbons
- Operating temperature to −50°:+80°

| ENCLOUSURE MOUNTING ACCESSORIES CPS-100 |   |
|---|---|
| CPS-100-0                               | Without Accessories   |
| CPS-100-1                               | Internal Support for Instrument                             |
| CPS-100-2                               | External Support for 2" Standpipe                           |
| CPS-100-3                               | External Support for Wall Mounting                          |
| INSTRUMENT LOOKING ACCESSORIES CPS-100  |   |
| CPS-100-x-0                             | Without window  |
| CPS-100-x-1                             | With window in macrolon                                     |
| INSTRUMENT MOUNTING ACCESSORIES CPS-100 |   |
| CPS-100-x-x-0                           | Without accessories   |
| CPS-100-x-x-1                           | With Assembly of Manifold and Fittings (supplied by client) |
| CPS-100-x-x-2                           | With Supply and Assembly of Manifold and Fittings           |
| HEADING ACCESSORIES CPS-100             |   |
| CPS-100-x-x-x-0                         | Without Insulation  |
| CPS-100-x-x-x-1                         | Internal Insulation — 20 mm thk                             |
| CPS-100-x-x-x-x-0                       | Without Electric Heater and Thermostat                      |
| CPS-100-x-x-x-x-1                       | Electrical Heater and Thermostat for safety area            |
| CPS-100-x-x-x-x-2                       | Electrical Heater and Thermostat for Hazardous area         |
| CPS-100-x-x-x-x-3                       | Heating with Steam Coil                                     |